

Dependent Resurvey of Portion of Subdivisional Lines  
in T. 31 S., R. 1 W.

CHAINS

A fir, 28 ins. diam., bears N.40\*E., 67 lks. dist.,  
mkd. 1/4 S. 15 B T.

A fir, 4 ins. diam., bears S.53\*E., 44 lks. dist.,  
mkd. 1/4 S 15 B T.

40.66 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground, for 1/4 sec. cor. of sec. 16 only, with  
brass cap marked

1/4 S16  
1923

from which

A fir, 20 ins. diam., bears S.51\*W., 44 lks. dist.,  
mkd. 1/4 S 16 B T.

A fir, 16 ins. diam., bears N.17\*W., 49 lks. dist.,  
mkd. 1/4 S 16 B T.

45.77 Spring branch, 1 lk. wide, course NW.

51.47 Spring branch, 2 lks. wide, course W.

79.36 Point of intersection of line bet. secs. 10 and 15, de-  
termined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground, for closing cor. of secs. 10 and 15, with  
brass cap marked

T31S  
S10  
S16 — CC  
S15  
RLW  
1923

from which

A fir, 16 ins. diam., bears N.84\*E., 41 lks. dist.,  
mkd. T 31 S R 1 W S 10 C C B T.

A fir, 7 ins. diam., bears S.22\*E., 11 lks. dist.,  
mkd. T 31 S R 1 W S 15 C C B T.

81.32 Top of flat ridge, divide bet. Elk Creek and Beaver Creek,  
bears NW. and SE.

The cor. established for secs. 9, 10, 15 and 16, located  
by reference to the original bearing trees. From cor.