

Dependent Resurvey of Portion of Subdivisional Lines  
in T. 31 S., R. 1 W.

CHAINS

point.

A fir, 18 ins. diam., bears N.8°E., 58 lks. dist.,  
mkd. T 31 S R 1 W S 10 B T. (Old B.T.)

A fir, 6 ins. diam., bears S.20°E., 100 lks. dist.,  
mkd. T 31 S R 1 W S 15 B T. (Old B.T.)

A fir, 20 ins. diam., bears S.51°W., 46 lks. dist.,  
mkd. T 31 S R 1 W S 16 B T. (New B.T.)

A fir, 18 ins. diam., bears N.1°W., 60 lks. dist.,  
mkd. T 31 S R 1 W S 9 B T. (Old B.T.)

The original bearing tree in sec. 16 is dead and  
fallen.

I now change this cor. to refer to secs. 9 and 16 only,  
and obliterate the marks on the bearing trees referring  
to secs. 10 and 15.

At exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in  
the ground, surrounded by a mound of stone, 2 ft. base,  
1 ft. high, for cor. of secs. 9 and 16 only, with  
brass cap marked

T31S  
S9  
— S10  
S16  
R1W  
1923

Land, mountainous.

Soil, rocky, 4th rate.

Timber, fir.

Undergrowth, vine maple.

N.89°17'W., bet. secs. 9 and 16.

Over mountainous land, through heavy timber and dense  
undergrowth.

Desc. 708 ft. to 1/4 sec. cor., over SW. slope.