

Dependent Resurvey of Portion of Subdivisional Lines  
in T. 31 S., R. 1 W.

CHAINS

- 9.81 Old trail, bears NW. and SE.
- 21.68 Devils Knob trail, bears NW. and SE.
- 28.35 Old Devils Knob trail, bears NW. and SE.
- 40.08 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked

.S9
1
—
4
S16
1923

from which

A yew, 10 ins. diam., bears S.81\*W., 36 lks. dist., mkd. 1/4 S 16 B T.

A fir, 8 ins. diam., bears N.18\*W., 23 lks. dist., mkd. 1/4 S 9 B T.

Desc. 55 ft. to

- 43.65 Creek, 4 lks. wide, course SW.; thence along broken S. slope.

68.30 Fence, bears NE. and SW.

71.53 Fence, bears NW. and SE.

80.16 The cor. of secs. 8, 9, 16 and 17, located by reference to the original bearing trees.

At exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap marked

T31S	R1W
S8	S9
—	
S17	S16
1923	

from which

An oak, 10 ins. diam., bears N.10\*E., 33 lks. dist., mkd. T 31 S R 1 W S 9 B T. (Old B.T.)

A pine, 24 ins. diam., bears S.47\*E., 43 lks. dist.,