

Dependent Resurvey of Portion of Subdivisional Lines
in T. 31 S., R. 1 W.

CHAINS

9).

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 4 only, with brass cap marked

1/4 S4
1923

from which

A yew, 6 ins. diam., bears N.31*E., 12 lks. dist.,
mkd. 1/4 S 4 B T.

A fir, 28 ins. diam., bears S.69*E., 25 lks. dist.,
mkd. 1/4 S 4 B T.

40.40 The point for the old 1/4 sec. cor. which I determine by reference to the original bearing trees.

I now change this cor. to refer to sec. 5 only, and

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 5 only, with brass cap marked

1/4 S5
1923

from which

A fir, 28 ins. diam., bears N.41*E., 50 lks. dist.,
mkd. 1/4 S B T. (Old B.T.)

A fir, 24 ins. diam., bears S.51*W., 15 lks. dist.,
mkd. 1/4 S 5 B T. (Old B.T.)

A cedar, 14 ins. diam., bears N.23*W., 30 lks. dist.,
mkd. 1/4 S 5 B T. (New B.T.)

Obliterate the marks on the bearing tree in sec. 4.

Thence

N.2*19'E.

28.60 Creek, 2 lks. wide, course NE.

40.55 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.

Land, mountainous.