

Subdivision of T. 31 S., R. 1 W.

CHAINS

the ground, for cor. of secs. 23, 24, 25 and 26, with
brass cap marked

T31S	R1W
S23	S24

S26	S25
1923	

from which

A fir, 20 ins. diam., bears N.89°E., 107 lks. dist.,
mkd. T 31 S R 1 W S 24 B T.

A fir, 16 ins. diam., bears S.40°E., 34 lks. dist.,
mkd. T 31 S R 1 W S 25 B T.

A fir, 30 ins. diam., bears S.63°W., 19 lks. dist.,
mkd. T 31 S R 1 W S 26 B T.

A fir, 32 ins. diam., bears N.23°W., 37 lks. dist.,
mkd. T 31 S R 1 W S 23 B T.

Land, mountainous.

Soil, rocky, 4th rate.

Timber, fir, and cedar.

Undergrowth, vine maple and hazel.

S.89°59'E., on a random line, bet. secs. 24 and 25.

40.00 Set temp. 1/4 sec. cor.

113.64 Intersect Willamette Meridian, 7 lks. N. of the cor. of
secs. 24 and 25 only, hereinbefore described.

Thence

N.89°57'W., on a true line, bet. secs. 24 and 25.

Over mountainous land, through heavy timber and dense
undergrowth.

Desc. 400 ft. over SW. slope.

26.09 Creek, 5 lks. wide, course NW.; asc. 160 ft. over NE.
slope.

34.10 Spur, slopes NW.; desc. 64 ft. over W. slope.

37.11 Gulch, course NE.; asc. 540 ft. over E. slope.

73.64 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in