

Subdivision of T. 31 S., R. 1 W.

CHAINS	in the ground, for 1/4 sec. cor., with brass cap marked
	S24 $\frac{1}{4}$ ——— S25 1923
	from which
	A fir, 30 ins. diam., bears S.15*W., 15 lks. dist., mkd. 1/4 S 25 B T.
	A fir, 22 ins. diam., bears N.17*W., 13 lks. dist., mkd. 1/4 S 24 B T.
87.85	Trail, bears N. and S.; telephone line, bears N. and S.
101.30	Top of ridge, 318 ft. above 1/4 sec. cor., divide bet. Elk Creek and Beaver Creek, bears NW. and SE.
	Trail, bears NW. and SE.
	Desc. 114 ft. over SW. slope.
113.64	The cor. of secs. 23, 24, 25, and 26. Land, mountainous. Soil, rocky, 4th rate. Timber, fir and cedar. Undergrowth, vine maple and snow brush.
	N.0*01'W., bet. secs. 23 and 24. Over mountainous land, through heavy timber and dense undergrowth. Asc. 100 ft. over SW. slope.
7.74	Top of ridge, divide bet. Elk Creek and Beaver Creek, bears NW. and SE.; old trail, bears NW. and SE. Devils Knob lookout, bears N.34*W., 22.00 chs. dist., Desc. 360 ft. over NE. slope.
11.88	Cut-off trail, bears E. and W.
18.50	Trail and telephone line, bears NW. and SE.
38.60	Asc. 20 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked