

Subdivision of T. 31 S., R. 1 W.

CHAINS

the ground, for 1/4 sec. cor. of sec. 9 only, with brass cap marked

1/4 S9  
1923

from which

A fir, 36 ins. diam., bears S.75\*W., 37 lks. dist., mkd. 1/4 S 9 B T.

A fir, 36 ins. diam., bears N.30\*W., 38 lks. dist., mkd. 1/4 S 9 B T.

Desc. 180 ft. to

49.83 Creek, 1 lk. wide, course NE.; continue descent, 50 ft. to

64.00 Asc. 12 ft. to

67.50 Top of spur, slopes NE.; desc. 280 ft. to

78.04 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 3 and 10 only, with brass cap marked

T31S  
S3  
S9  
S10  
R1W  
1923

from which

A fir, 26 ins. diam., bears N.56\*E., 23 lks. dist., mkd. T 31 S R 1 W S 3 B T.

A yew, 14 ins. diam., bears S.45\*E., 58 lks. dist., mkd. T 31 S R 1 W S 10 B T.

78.65 Creek, 2 lks. wide, course NE.

82.09 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4 and 9 only, with brass cap marked

T31S  
S4  
S3  
S9  
R1W  
1923