

Retracement of Portion of South Boundary
of T. 31 S., R. 1 W.

CHAINS

brass cap marked

| | |
|------|-----|
| T31S | R1W |
| S31 | S32 |
| | |
| T32S | R1W |
| S6 | |
| 1923 | |

from which

A cedar, 16 ins. diam., bears N.38*E., 67 lks. dist.,
mkd. T 31 S R 1 W S 32 B T. (New B T.)

Thence

West, retracing S. bdy. of sec. 31.

Over mountainous land, through heavy timber and dense
undergrowth.

Asc. 656 ft. over NE. slope.

36.96 Summit of high ridge, bears NE. and SW.; desc. 70 ft.
over steep NW. slope.

40.43 Intersect the closing cor. of Tps. 32 S., Rs. 1 and 2 W.,
which is a basalt stone, firmly set, 5x12x12 ins. above
ground, marked C C on S., with 6 notches on S., E. and
W. edges; from which

A fir, 15 ins. diam., bears N.70*E., 11 lks. dist.,
mkd. C C T 31 S R 1 W S 31 B T. (Old B T.)

A fir, 55 ins. diam., bears S.55*E., 5 lks. dist.,
mkd. C C T 32 S R 1 W S 6 B T. (Old B T.)

A fir, 35 ins. diam., bears S.37*W., 15 lks. dist.,
mkd. C C T 32 S R 2 W S 1 B T. (Old B T.)

Obliterate the marks on the old bearing tree in sec. 31,

40.67 Intersect the old 1/4 sec. cor., which is a fir, 18 ins.
diam., with marks overgrown; from which

A fir, 30 ins. diam., bears N.50*E., 27 lks. dist.,
mkd. 1/4 S B T. (Old B T.)

A fir, 40 ins. diam., bears S.30*E., 14 lks. dist.,
mkd. 1/4 S B T (Old B T.)

I now change this cor. to refer to sec. 31 only, and ob-