

County Surveyor's Record, Douglas County, Oregon

130

Retracement of Portion of Subdivisional Lines
of T. 31 S., R. 1 W.

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in. the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap marked

T31S	R1W
S19	S20
S30	S29
1923	

from which

A fir, 20 ins. diam., bears N.15°E., 36 lks. dist., mkd. T 31 S R 1 W S 20 B T. (Old B T.)

A fir, 18 ins. diam., bears S.4°E., 72 lks. dist., mkd. T 31 S R 1 W S 29 B T. (Old B T.)

A fir, 20 ins. diam., bears S.21½°W., 76 lks. dist., mkd. T 31 S R 1 W S 30 B T. (Old B T.)

A fir, 20 ins. diam., bears N.85°W., 62 lks. dist., mkd. T 31 S R 1 W S 19 B T. (Old B T.)

Thence

S.89°12'W., resurveying bet. secs. 19 and 30.

Over mountainous land, through heavy timber and dense undergrowth.

Desc. 55 ft. over SW. slope.

4.08 California-Oregon Power Co. transmission line, bears NW. and SE.

5.64 Road, bears NW. and SE.

7.34 Elk Creek, 30 lks. wide, course NW.; asc. 280 ft. over NE. slope.

37.90 Ridge, bears N. and S.; desc. 50 ft. over W. slope.

40.47 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S19
1/4
S30
1923

from which