

County Surveyor's Record, Douglas County, Oregon

132

Retracement of Portion of Subdivisional Lines
of T. 31 S., R. 1 W.

CHAINS

$\frac{1}{4}$ S30 S29 1923

from which

A fir 18 ins. diam., bears S.22*E., 25 lks. dist.,
now mkd. 1/4 S 29 B T. (Old B T.)

A fir, 18 ins. diam., bears N.60*W., 18 lks. dist.,
now mkd. 1/4 S 30 B T. (Old B T.)

Asc. 127 ft. to

51.00 Desc. 83 ft. to

61.07 Spring branch. 1 lk. wide, course E.; asc. 233 ft.

82.19 Fall 27 lks. W. of the point for the cor. of secs. 29, 30
31, and 32, which I locate by reference to the original
bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 29, 30, 31 and 32, with
brass cap marked

<table style="border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T31S</td> <td style="padding: 2px;">R1W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S30</td> <td style="padding: 2px;">S29</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S31</td> <td style="padding: 2px;">S32</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1923</td> </tr> </table>	T31S	R1W	S30	S29			S31	S32	1923	
T31S	R1W									
S30	S29									
S31	S32									
1923										

from which

A cedar, 20 ins. diam., bears N.12*E., 65 lks. dist.,
mkd. T 31 S R 1 W S 29 B T. (New B T.)

A fir, 18 ins. diam., bears S.80*E., 3 lks. dist.,
mkd. T 31 S R 1 W S 32 B T. (Old B T.)

A fir, 30 ins. diam., bears S.53*W., 28 lks. dist.,
mkd. T 31 S R 1 W S 31 B T. (New B T.)

A cedar, 18 ins. diam., bears N.8*W., 20 lks. dist.,
mkd. T 31 S R 1 W S 30 B T. (Old B T.)

The original bearing trees in secs. 29 and 31 are
dead and fallen.