

## County Surveyor's Record, Douglas County, Oregon

## Retracements of the South Boundary of T. 31 S., R. 2 W.

## CHAINS

39.85 The cor. of secs. 35 & 36 which is an ironstone 6x8x4 ins. above ground firmly set, marked and witnessed as described by the surveyor general  
October 21, 1906

Thence I retrace

S.89°58'W., on South Boundary sec. 35

38.05 The cor. of secs. 2 & 3 T. 32 S., R. 2 W., which is a basalt stone 7x10x6 ins. above ground firmly set and marked and witnessed as described by the surveyor general

39.55 The  $\frac{1}{4}$  sec. cor. on South Boundary sec. 35 which is a basalt stone 6x10x4 ins. above ground, firmly set and marked and witnessed as described by the surveyor general

Commencing at the  $\frac{1}{4}$  sec. cor. I run

S.89°58'W., on South Boundary sec. 35

39.70 The cor. of secs. 34 & 35 which is an ironstone 6x8x8 ins. above ground firmly set, marked and witnessed as described by the surveyor general

S.89°58'W., on South Boundary sec. 34

38.19 The closing cor. of secs. 3 & 4 T. 32 S., R. 2 W., which is a basalt stone 6x10x8 ins. above ground firmly set, marked and witnessed as described by the surveyor general, bears South 12 lks. dist.

39.60 The  $\frac{1}{4}$  sec. cor. on South Boundary secs. 34 which is an ironstone 6x10x10 ins. above ground, firmly set, and marked and witnessed as described by the surveyor general bears South 12 lks. dist.

The course of this line is S.89°48'W.

Commencing at the  $\frac{1}{4}$  sec. cor. I retrace

S.89°58'W., on South Boundary sec. 34

39.49 The cor. of secs. 33 & 34 which is an ironstone 7x10x10 ins. above ground, firmly set and marked and witnessed as described by the surveyor general bears South 20 lks. dist.

The course of this line is 89°41'W.

October 22, 1906

Thence I retrace

S.89°58'W., on South Boundary sec. 33