

County Surveyor's Record, Douglas County, Oregon

7637

Subdivisions of T. 31 S., R. 2 W.

CHAINS	80.00	October 26, 1906
	<p>Thence I run West on sec. cor. line bet. secs. 30 & 31 Over Mountainous land, heavily timbered and covered with dense undergrowth Along North slope</p>	
1.50	Ridge point descending NW	
3.00	Ravine course NW	
5.75	Creek, 1 lk. wide, course NW	
9.25	Ridge Point descending NW	
17.15	Creek 1 lk. wide, course NW	
21.00	Ridge bears NW & SE	
25.75	Creek, 1 lk. wide, course NW	
31.00	Creek 1 lk. wide, course NW	
37.25	Callahan Creek, 4 lks. wide, course N.	
40.00	<p>Set a Granite stone 15x8x6 ins. 10 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N face from which A Cedar, 6 ins. diam., bears N.70*W., 30 lks. dist. Marked $\frac{1}{4}$ S 30 B T A Hemlock, 12 ins. diam., bears S.37*W., 43 lks. dist. Marked $\frac{1}{4}$ S 31 B T</p>	
	Ascend SE slope	
48.68	<p>Intersect W. bdy. of the T. 6.23 chs. N of the cor. of secs. 25, 30, 31 & 36 which is a granite stone 6x12x10 ins. above ground firmly set, marked and witnessed as described by the surveyor general</p> <p>Set a slate stone 18x9x6 ins. 12 ins. in the ground for closing cor. of secs. 30 & 31 marked CC on E with 5 grooves on N and 1 groove on S face from which A Fir, 36 ins. diam., bears N.40*E., 17 lks. dist., Marked T 31 S R 2 W S 30 B T A Fir, 12 ins. diam., bears S48*E., 36 lks. dist., Marked T 31 S R 2 W S 31 B T</p>	
	<p>Destroy marks on bearing trees at former cor. referring to secs. 30 & 31</p>	