

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 2 W.

CHAINS

June 22, 1908

Thence I run

N.0°4'W., bet. secs. 29 &amp; 30

Over Mountainous land, heavily timbered and covered with  
dense undergrowth

Descend NW slope

11.25 Creek, 2 lks. wide, course NW

15.75 Ridge point descending NW

17.50 Creek, 1 lk. wide, course W

27.75 Ridge bears NW &amp; SE

37.25 Creek, 1 lk. wide, course N.60°W.

40.00 No stones obtainable

Set a Fir Post 3 ft. long 4 ins. sq. 24 ins. in the  
ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S 30 on W and 29 on E  
face from whichA Cedar, 20 ins. diam., bears S.53 $\frac{1}{2}$ °E., 21 lks.  
dist., Marked  $\frac{1}{4}$  S 29 B TA Fir, 6 ins. diam., bears S.67 $\frac{1}{2}$ °W., 45 lks. dist.,  
Marked  $\frac{1}{4}$  S 30 B T

48.75 Ridge Point descending W

56.75 Callahan Creek, 8 lks. wide, course NE

Ascend N slope

68.50 Creek, 3 lks. wide, course S.60°E.

80.00 A Madrone, 15 ins. diam., for cor. of secs. 19, 20, 29  
& 30 I mark

T 31 S S 20 on NE

R 2 W S 29 on SE

S 30 on SW and

S 19 on NW side, with 2 notches on S and 5 notches  
on E side from whichA Fir, 9 ins. diam., bears N.32 $\frac{1}{2}$ °E., 51 lks.  
dist., Marked T 31 S R 2 W S 20 B TA Madrone, 18 ins. diam., bears S.70°E., 24 lks  
dist., Marked T 31 S R 2 W S 29 B T

A Fir, 20 ins. diam., bears S.14°W., 26 lks.