

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 2 W.

CHAINS

Set A Fir Post 3 ft. long 4 ins. sq. 24 ins. in the ground for cor. of secs., 17, 18, 19 & 20 marked

T 31 S 17 on NE

R 2 W S 20 on SE

S 19 on SW and

S 18 on NW face with 3 notches on S and 5 notches on E edge from which

A Fir, 30 ins. diam., bears N.50°E., 189 lks.

dist., Marked T 31 S R 2 W S 17 B T

A Hemlock, 6 ins. diam., bears S.48°E., 64 lks.

dist., Marked T 31 S R 2 W S 20 B T

A Fir, 6 ins. diam., bears S.20°W., 68 lks. dist

Marked T 31 S R 2 W S 19 B T

A Fir, 30 ins. diam., bears N.28½°W., 56 lks.

dist., Marked T 31 S R 2 W S 18 B T

Land Mountainous

Soil, Granite 3rd. rate

Timber, Fir, Hemlock; Undergrowth, Hemlock, Madone, Lilac

Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey.

80.00 chs.

June 24, 1908

Thence I run

S.89°56'E. on a random line bet. secs. 17 & 20

40.00 Set Temp. ½ sec. cor.

79.60 Intersect West boundary sec. 21, 3.17 chs. S.0°3'E. of the Temp. closing cor. set June 20 at termination of random line bet. secs. 20 & 21

No stone obtainable

Set a Fir Post 3 ft. long 4 ins. sq. 24 ins. in the ground for closing cor. of secs. 17 & 20 marked

S 17 on N

S 20 on S and

CC T 31 S R 2 W on W face with 3 grooves on N & S