

County Surveyor's Record, Douglas County, Oregon

Retracement of Subdivisions of T. 31 S., R. 2 W.

CHAINS

I reestablish the cor. in its original position as follows

The original cor.

A Madrone, 12 ins. diam. for $\frac{1}{4}$ sec. cor.

I re-mark $\frac{1}{4}$ S 22 on N and 27 on S side from which

A Madrone, 16 ins. diam., bears N.30*W., 24 lks. dist.

Marked $\frac{1}{4}$ S 22 B T

A Madrone, 16 ins. diam., bears S.70*W., 100 lks. dist.

Marked $\frac{1}{4}$ S 27 B T

The course of this line is East and the distance is 40.50 chains.

Commencing at the $\frac{1}{4}$ sec. cor. I run

East bet. secs. 22 & 27

19.00 Summit of butte

Descend E slope

23.75 Wagon Road to Banfield Copper Mine bears N & S

30.25 Trail bears NW & SE

40.25 The cor. of secs. 22 & 23

The course of this line is East and the distance is 40.25 chains

Land Mountainous

Soil, stony, 2nd. & 3rd. rate

Timber, Fir, Pine, Madrone, Cedar; Undergrowth, Fir, Cedar, Madrone, Hazel

Mountainous or heavily timbered land or land covered with dense Undergrowth and exceptionally difficult to survey. 80.75 chains.

June 17, 1908

At the cor. of secs. 21, & 22 on N boundary sec. 28

Thence I run

West bet. secs. 21 & 28

Over Mountainous land, across rocky opening

Ascend SE slope

17.30 Creek, 2 lks. wide, course S.60*E.

Enter heavy timber and dense undergrowth, bears NW & SE