

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 3 W.

CHAINS		
7.50	Leave heavy timber; enter dense brush.	
16.00	Ascend in heavy timber.	+50
21.00	Descend.	-600
37.80	A stream, 15 lks. wide, course NW; ascend.	+250
40.00	Set a stone, 14x12x5 ins. 9 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face; from which A fir, 7 ins. diam., bears S.38-3/4*E., 16-3/4 lks. dist., marked $\frac{1}{4}$ S B T. A yew, 6 ins. diam., bears N.25*W., 5 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S B T.	
45.00	A gulch, course NE and SW.	
58.30	Descend.	-100
60.50	A gulch, course NE and SW; ascend.	+40
61.80	Descend.	-150
63.50	A gulch, course NE and SW; ascend.	+25
64.30	Descend.	-50
65.10	A gulch, course NE and SW; ascend.	+250
72.20	A fir, 20 ins. diam., on line marked with 2 notches on N and S sides.	
90.15	Summit of ridge, course N.15*E., and S.15*W; descend.	-125
100.52	Intersect the N bdy. of the tp. 7.20 chs. W of the $\frac{1}{4}$ sec. cor. on S bdy. of sec. 35, T 30 S. R. 3 W., which is a hemlock, 5 ins. diam., marked $\frac{1}{4}$ S on N face; from which A fir, 22 ins. diam., bears S.62 $\frac{1}{2}$ *W., 23 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 30 ins. diam., bears N.79 $\frac{1}{4}$ *W., 38 lks. dist. marked $\frac{1}{4}$ S B T. At point of intersection, set a laurel post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for closing cor. to secs. 2 and 3, marked C C T 31 S R 3 W on S S 2 on E and S 3 on W faces, with 2 notches on E and 4 notches on W faces; from which A laurel, 9 ins. diam., bears S.67*E., 82 $\frac{1}{2}$ lks. dist.	