

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 3 W.

CHAINS		
5.25	A ravine, course E and W; ascend.	+40
8.50	Summit of spur, course E and W; descend.	-150
16.00	A ravine, course E and W; ascend.	+50
22.30	A cedar, 40 ins. diam., on line marked with 2 notches on N and S sides and descend.	-300
28.60	A ravine, course E and W; ascend.	+50
35.50	Descend.	-1250
40.00	Set a stone, 12x8x6 ins. 8 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face; from which A fir, 14 ins. diam., bears N.40 $\frac{1}{2}$ *E., 17 lks. dist., marked $\frac{1}{4}$ S B T. A cedar, 11 ins. diam., bears N.35 $\frac{1}{2}$ *W., 39 lks. dist., marked $\frac{1}{4}$ S B T.	
60.75	A spring branch, 1 lk. wide, course N.10*W.	
61.75	W Fork Stout's Creek, 30 lks. wide, course NE; ascend.	+300
80.00	A ravine, course SE and NW.	
83.25	Descend.	-250
97.00	Ascend.	+30
98.00	Descend.	-40
101.03	Intersect the N bdy. of the tp. 6.60 chs. W of the $\frac{1}{4}$ sec. cor. on S bdy. of sec. 34, T 30 S., R 3 W., which is a post, 4 ins. sq., marked $\frac{1}{4}$ S on N face, from which A maple, 13 ins. diam., bears S.66 $\frac{1}{2}$ *E., 9 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 5 ins. diam., bears N.54 $\frac{1}{2}$ *W., 47 lks. dist., marked $\frac{1}{4}$ S B T. At point of intersection, set a fir post, 5 ft. long, 4 ins. sq., 24 ins. in the ground, for closing cor. to secs. 3 and 4, marked C C T 31 S R 3 W on S S 3 on E and S 4 on W faces, with 3 notches on E and W faces; from which A laurel, 20 ins. diam., bears S.11*E., 29 $\frac{1}{2}$ lks.	