

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 3 W.

CHAINS		
	N.0*3'W., on a true line, bet. secs. 4 and 5.	
		Va.19*E.
	Descend steeply.	-200
6.00	A stream, 3 lks. wide, course SE; ascend.	+200
27.50	Summit of spur, course E and W; descend.	-1000
36.80	A fir, 36 ins. diam., on line marked with 2 notches on N and S sides.	
40.00	Set a stone, 11x11x5 ins. 7 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face; from which A fir, 10 ins. diam., bears S.15*E., 16 lks. dist., marked $\frac{1}{4}$ S B T. A laurel, 10 ins. diam., bears S.72 $\frac{1}{2}$ *W., 30 lks. dist., marked $\frac{1}{4}$ S B T.	
47.50	A stream, 10 lks. wide, course E; ascend.	+400
54.23	A fir, 36 ins. diam., on line marked with 2 notches on N and S sides.	
61.00	Leave heavy timber; enter dense brush.	
68.25	Descend.	-225
71.00	Enter heavy timber.	
78.75	A ravine, course E and W and ascend.	+100
87.25	Summit of spur, course NE and SW; descend.	-150
97.00	A stream, 2 lks. wide, course NE; ascend.	+50
101.40	Intersect the N bdy. of the tp. 2.80 chs. W of the $\frac{1}{4}$ sec. cor. on S bdy. of sec. 33, T 30 S., R. 3 W., which is a stone, 10x8x4 ins. above ground, marked $\frac{1}{4}$ on N face; from which A fir, 16 ins. diam., bears N.4 $\frac{1}{2}$ *E., 12-3/4 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 5 ft. diam., bears S.72 $\frac{1}{2}$ *E., 28 lks. dist., marked $\frac{1}{4}$ S B T. At point of intersection, set a stone, 12x10x10 ins., 8 ins. in the ground, for closing cor. to secs. 4 and	