

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 3 W.

CHAINS		
	sec. cor. marked $\frac{1}{4}$ on W face; from which	
	A fir, 16 ins. diam., bears S.12 $\frac{1}{2}$ *E., 12 lks.	
	dist., marked $\frac{1}{4}$ S B T.	
	A fir, 16 ins. diam., bears S.51-3/4*W., 38 $\frac{1}{4}$ lks.	
	dist., marked $\frac{1}{4}$ S B T.	
44.00	Descend.	-500
56.00	A stream, 2 lks. wide, course N.75*W., ascend.	+500
71.00	Summit of ridge, course E and W; descend.	-40
74.75	Ascend.	+40
76.25	Descend.	-450
78.35	A fir, 36 ins. diam., on line marked with 2 notches on N and S sides.	
94.05	A stream, 3 lks. wide, course NW; ascend.	+75
	May 6, 1894.	
100.00	Descend.	-40
102.30	Intersect the N bdy. of the tp. 2.07 chs. W of the $\frac{1}{4}$ sec. cor. on S bdy. of sec. 32, T 30 S., R. 3 W., which is a stone, 12x8x4 ins. above ground, marked $\frac{1}{4}$ on N face; from which	
	A fir, 30 ins. diam., bears N.71 $\frac{1}{2}$ *E., 15 $\frac{1}{2}$ lks.	
	dist., marked $\frac{1}{4}$ S B T.	
	A live oak, 10 ins. diam., bears S.15*W., 47 $\frac{1}{2}$ lks.	
	dist., marked $\frac{1}{4}$ S B T.	
	At point of intersection, set a stone, 20x8x8 ins. 15 ins. in the ground for closing cor. to secs. 5 and 6, marked C C on S with 5 notches on E and 1 notch on W faces; from which	
	A fir, 22 ins. diam., bears S.64 $\frac{1}{4}$ *E., 28 lks.	
	dist., marked T 31 S R 3 W S 5 B T.	
	A maple, 8 ins. diam., bears S.33*W., 24 lks.	
	dist., marked T 31 S R 3 W S 6 B T.	
	A laurel, 10 ins. diam., bears N.30*W., 10 $\frac{1}{4}$ lks.	
	dist., marked T 31 S R 3 W C C S 5 and 6 B T.	