

County Surveyor's Record, Douglas County, Oregon

South boundary of T. 31 S., R. 4 W.,  
 As surveyed by W. H. Byars, Deputy Surveyor,  
 Under contract No. 152, dated June 3, 1871.

CHAINS

	Begin at the post, the established cor., to Tps., 31 and 32 S., Rs., 4 and 5 W.	
	The witness trees all destroyed except one. Stake rotted off at the ground, stub remaining in place. Witness tree.	
	A fir, 24 ins. diam., bears N.62*E., 33 lks. dist.	
	From this corner I run	
	East, on a true line, bet. secs. 6 and 31.	Va. 18' 40" E.
2.00	Begin descent.	
40.00	Set $\frac{1}{4}$ sec. post, from which	-1800
	A fir, 20 ins. diam., bears N.20*E., 40 lks. dist.	
	A fir, 30 ins. diam., bears S.45*W., 9 lks. dist.	
45.00	Enter vine maple, bottom course N and S.	-1900
48.80	A creek, 3 lks. wide, course S.	-1925
70.00	A creek, 3 lks. wide, course S.	-1925
72.50	Begin ascent.	-1900
80.00	Set post, cor. to secs. 5, 6, 31 and 32 from which	1600
	A fir, 14 ins. diam., bears N.52*E., 29 lks. dist.	
	A laurel, 8 ins. diam., bears S.40*E., 12 lks. dist.	
	A laurel, 5 ins. diam., bears S.20*W., 26 lks. dist.	
	A laurel, 6 ins. diam., bears N.78*W., 9 lks. dist.	
	Land, W and E parts mountainous; middle part level.	
	Soil, 2d rate.	
	Timber, good fir, cedar, pine, laurel, oaks and alder.	
	East on a true line, bet. secs. 5 and 32.	
		Va. 20*E.
2.00	Top of spur, course S.	+40
5.00	Begin descent.	40
12.00	A flat bench.	
25.75	A dry creek, course S.	-25
26.00	Begin ascent.	-25
34.25	A pine, 30 ins. diam., top of spur, course S.	+50