

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 4 W.

CHAINS

banks. A mill seat may be found almost anywhere. Two settlements are now in the Tp. viz., on SE and SW $\frac{1}{4}$ of sec. 33. Also in sec. 27. Boundaries of claim not ascertained.

East Boundary of T. 31 S., R. 4 W.
As surveyed by William M. Bushey, Deputy Surveyor
under contract No. 620, dated June 17, 1893

I begin at the cor. to secs. 25, 30, 31 and 36, on the E bdy. which is a post, considerably decayed, marked T 31 S S 30 on NE., R 3 W S 31 on SE., R 4 W S 36 on SW., and S 25 on NW faces with 5 notches on N and 1 notch on S edges; I remove this post and set a stone 22x18x7 ins., 16 ins. in the ground for cor. to secs. 25, 30, 31 and 36, marked with 5 notches on N and 1 notch on S edges; from which

A laurel, 16 ins. diam., bears S.72*E., 8 lks.
dist., marked T 31 S R 3 W S 31 B T.

A fir, 12 ins. diam., bears N.25*W., 29 lks.
dist., marked T 31 S R 4 W S 25 B T.

The witness trees in secs. 30 and 36 are blown over and the laurel witness tree in sec. 31 is dead. I, therefore, mark 3 new witness trees as follows

A fir, 20 ins. diam., bears N.6 $\frac{1}{2}$ *E., 34 $\frac{1}{2}$ lks.
dist., marked T 31 S R 3 W S 30 B T.

A fir, 10 ins. diam., bears S.26 $\frac{1}{2}$ *E., 47 $\frac{1}{2}$ lks.
dist., marked T 31 S R 3 W S 31 B T.

A cedar, 26 $\frac{1}{2}$ ins. diam., bears S.12 $\frac{1}{2}$ *W., 33 lks.
dist., marked T 31 S R 4 W S 36 B T.

Thence I run

North, bet. secs. 25 and 30.

Va.19*E.

Ascend in windfall and brush.

2.05 A spring branch, 1 lk. wide, course N.80*W.

+600