

24
County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 4 W.

CHAINS

A willow, 5 ins. diam., (6 ins. now) bears
N.45*E., 14 lks. dist., marked T 31 S R 3 W
S 31 B T.

A willow, 5 ins. diam., (7 ins. now) bears
S.48*E., 11 lks. dist., marked T 32 S R 3 W
S 6 B T.

A willow, 5 ins. diam., bears S.50*W., 9 lks.
dist., marked T 32 S R 4 W S 1 B T.

A willow, 5 ins. diam., bears N.45*W., 13 lks.
dist., marked T 31 S R 4 W S 36 B T.

From the tp. cor. I run

North, on East bdy. of sec. 36.

Va.19 $\frac{1}{2}$ *E.

At 39.92 chs. find $\frac{1}{4}$ sec. cor. 6 lks. W and at 79.93
chs., find the cor. to secs. 25 and 36, 4 lks. W
of my line. I now return to the SE cor. of the tp.

Thence I run

West, along South bdy. of sec. 36.

Va.19 $\frac{1}{2}$ *E.

At 40.08 chs. find $\frac{1}{4}$ sec. cor. 10 lks. S and at
80.20 chs. find cor. to secs. 35 and 36, 8 lks. S.
Therefore the bearings and lengths of these lines
practically agree with the field notes furnished me by
the surveyor general. With the above named true
bearings the subdivision lines^s of the eastern tier
of sections will be run as required by the printed
instructions.