

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 31 S., R. 4 W.

CHAINS

to secs. 13, 14, 23 and 24, marked with 1 notch on E and 3 notches on S edges; from which

A fir, 11 ins. diam., bears N.71*E., 9 1/2 lks. dist., marked T 31 S R 4 W S 13 B T.

A fir, 15 ins. diam., bears S.69*E., 55 lks. dist., marked T 31 S R 4 W S 24 B T.

A fir, 16 ins. diam., bears S.29*W., 10 lks. dist., marked T 31 S R 4 W S 23 B T.

A fir, 12 ins. diam., bears N.35*W., 39 lks. dist. marked T 31 S R 4 W S 14 B T.

Land, mountainous, 80.00 chs.

Soil, 3d rate.

Heavily timbered with fir, laurel, cedar, chinquapin, and maple, 80.00 chs.

Dense undergrowth of laurel, madrone, vine maple, arrow-wood and chinquapin, 75.00 chs.

S.89*38'E., on random line, bet. secs. 13 and 24.

Va.19*E.

40.00 Set temp. 1/4 sec. cor.

80.72 Intersect the E bdy. of the tp. 38 lks. N of the cor. to secs. 13, 18, 19 and 24.

Thence I run

N.89*22'W., on a true line, bet. secs. 13 and 24.

Va.19*E.

Ascend.

+225

10.00 Summit of spur, course N and S ; descend.

-175

20.30 A ravine, course N and S, water in holes; ascend

+150

July 6, 1894.

26.40 Summit of spur, course N and S; descend.

-400

40.36 Set a stone, 14x12x8 ins., 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N face, from which

A fir, 9 ins. diam., bears N.17 1/4 *E., 16 lks. dist.,