

76
County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 31 S., R. 4 W.

CHAINS

A fir, 24 ins. diam., bears S.36*W., 35 lks. dist.,
marked T 31 S R 5 W S 36 B T.

A fir, 16 ins. diam., (24 ins. diam.,) bears
N.54*W., 31 lks. dist., marked T 31 S R 5 W S
25 B T.

As this closing is not within the prescribed limit
for closing, I begin at the cor. established for
secs. 25, 30, 31 and 36.

Thence I run

South, on a blank line, bet. secs. 31 and 36.

Va.18-3/4*E.

Descend.

-60

2.50 A stream, 1 lk. wide, course SE; ascend.

+50

5.25 Descend. July 27, 1894.

-50

7.75 Ascend.

+40

11.75 Descend.

-75

17.75 A stream, 3 lks. wide, course SE; ascend.

+60

29.00 Descend.

-175

37.80 A stream, 8 lks. wide, course SE; ascend.

+600

39.90 Set temp. post. The 1/4 sec. cor. is gone. I find the
2 original bearing trees.

At cor, point

Set a stone, 10x10x8 ins. 7 ins. in the ground, for 1/4
sec. cor. marked 1/4 on W face; from which

A maple, 12 ins. diam., (16 ins. now) bears
N.52*E., 54 lks. dist., marked 1/4 S B T.

A vine maple, 4 ins. diam., (7 ins. now) bears
S.70*W., 10 lks. dist., marked 1/4 S B T.

I measure W to temp. post, 18 lks. dist.

50.00 A ravine, course NE and SW.

60.00 Descend.

-75

65.75 A stream, 1 lk. wide, course SE; ascend.

+90

70.00 Descend.

-150

76.25 A stream, 1 lk. wide, course SE; ascend.

+80