

County Surveyor's Record, Douglas County, Oregon

7877

Exterior Lines, Tp. 31 S., R. 5 W., W. M.
 As surveyed by Geo. W. Hyde, Deputy Surveyor
 Under contract No. 54, dated Feb. 19, 1855

CHAINS

Va. 18°35'E.

	South, on West boundary of sec. 6	
	Begin ascent of NW. slope.	
15.00	Summit of Ridge C. NW. and SE.	+350
33.50	A fir, 36 ins. diam., begin on NW. slope.	+150
40.00	A fir, 4 ins. diam., is $\frac{1}{4}$ sec. cor., from which	+180
	A laurel, 3 ins. diam., bears N.15°E., 24 lks. dis.	
	A fir, 6 ins. diam., bears S.87°W., 8 lks. dist.	
42.50	Top of high ridge c E. & SW., begin SE. slope	+100
62.50	A fir, 20 ins. diam.,	-160
75.00	Leave SE. and begin S. desc.	-80
77.75	A dry ravine c E.	-250
80.00	Set post cor. to secs. 1, 6, 7 & 12, from which	+120
	A fir, 6 ins. diam., bears S.18°E., 6 lks. dist.	
	A fir, 6 ins. diam., bears N.35°E., 29 lks. dist.	
	A fir, 6 ins. diam., bears N.20°W., 35 lks. dist.	
	A fir, 8 ins. diam., bears S.77°W., 60 lks. dist.	
	Rough rocky mountains, unfit for settlement.	

Va. 18°30'E.

	South, on West boundary of sec. 7	
7.50	Summit on E. slope of ridge	+200
19.10	A fir, 30 ins. diam.,	
21.00	Ravine (dry) c E.	+150
37.50	Summit of E. slope of ridge.	+180
40.00	Set $\frac{1}{4}$ sec. post, from which	-100
	A fir, 6 ins. diam., bears N.66 $\frac{1}{2}$ °E., 38 lks. dist.	
	A fir, 8 ins. diam., bears S.48°W., 13 lks. dist.	
44.50	Ravine and branch, 5 lks. wide, c N.30°E.	-80
54.00	Leave same c N. and from N.20°W.	+60
65.00	Summit on line of NW. slope.	+250
67.50	Branch, 2 lks. wide, c NW.	-80
80.00	Set post c to secs. 7, 12, 13, 18.	+480