

County Surveyor's Record, Douglas County, Oregon

General description, continued, T. 31 S., R. 5 W.

CHAINS

Saw vast quantity of Quartz broken in small pieces. I believe there are claimed several valuable mineral ledges in sec. 5 but as yet they are not prospected enough to determine their value.

Subdivisions of T. 31 S., R. 5 W.,  
As surveyed by W. H. Byars, U. S. Deputy Surveyor.  
Under Contract No. 456, dated July 28, 1882.

I commenced at the cor. to secs. 1, 2, 35 and 36 on South boundary, which is a fir post, 4 ins. square, firmly set in the ground, marked T 31 S R 5 W S 36 on NE. face, T 32 S S 1 on SE. face, S 2 on SW. face, and S 35 on NW. face, from which

A laurel, 10 ins. diam., bears N.65\*E., 52 lks.

Marked T 31 S R 5 W S 36 B T.

A cedar, 60 ins. diam., bears S.84\*E., 26 lks.

Marked T 32 S R 5 W S 1 B T.

A laurel, 36 ins. diam., bears S.43\*W., 73 lks.

Marked T 32 S R 5 W S 2 B T.

A laurel, 12 ins. diam., bears N.65\*W., 26 lks.

Marked T 31 S R 5 W S 35 B T.

Thence I run North between secs. 35 and 36.

Va. 19\*E.

Ascend.

12.50 Ascend along steep E. slope.

23.50 Top of ridge course NE. and S.20\*W.

Descend NW. slope.

30.00 Very steep descent.

40.00 Set a fir post, 4 ft. long, 3 ins. square, 20 ins. in ground, marked  $\frac{1}{2}$  S on the W. side for the  $\frac{1}{2}$  sec. cor., from which

A fir, 12 ins. diam., bears S.78\*E., 14 lks. dist.

Marked  $\frac{1}{2}$  S B T.