

Subdivisions of T. 31 S., R. 5 W.

CHAINS

post firmly set in ground and properly marked, from which

A laurel, 12 ins. diam., bears N.48*E., 43 lks.

Marked T 31 S R 4 W S 19 B T.

A fir, 7 ins. diam., bears S.10*E., 62 lks. dist.

Marked T 31 S R 4 W S 30 B T.

A fir, 4 ins. diam., bears S.68*W., 41 lks. dist.

Marked T 31 S R 5 W S 25 B T.

A laurel, 8 ins. diam., bears N.28*W., 41 lks.

Marked T 31 S R 5 W S 24 B T.

Thence I run

S.89*30'W., on a true line between secs. 24 and 25 with
same var.

- 40.32 Set a sandstone 15x15x8 ins., 12 ins. in ground, marked
¼ on N. face for the sec. cor., from which
- A fir, 15 ins. diam., bears N.23*E., 74 lks. dist.
- Marked ¼ S B T.
- A laurel, 14 ins. diam., bears S.60*E., 24 lks.
- Marked ¼ S B T.

- 80.64 The corner to sections 23, 24, 25 & 26.
Land, rough and mountainous.
Soil, third rate.
Dense forests of fir, cedar and laurel.
Thick undergrowth of fir, cedar, & hazel.

Va. 19*E.

North, between sections 23 and 24.

- 0.20 Stage Road, c N.75*W. and S.75*E.
- 3.00 Same road, c N.15*E.
- 7.50 Canyon creek, 20 lks. wide, c N.20*E.
Ascend along steep East slope of mountain.
- 40.00 Set a basalt stone, 18x13x12 ins., 12 ins. in ground,
marked ¼ on West side for the ¼ sec. cor., from which