

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 5 W.

CHAINS

- 40.00 Set a Basalt stone, 20x12x8 ins., 15 ins. in ground, marked $\frac{1}{4}$ on W. side for the $\frac{1}{4}$ sec. cor., from which
- A Live Oak, 15 ins. diam., bears N.62*E., 125 lks.
Marked $\frac{1}{4}$ S B T.
- A Fir, 26 ins. diam., bears N.63*W., 164lks. dis.
Marked $\frac{1}{4}$ S B T.
- 63.00 Top of high range, c SE. Descend steep NE. slope.
- 80.00 Set a dogwood post, 4 feet long, 4 ins. square, 20 ins. in ground, marked T 31 S R 5 W S 2 on NE. face S 11, on S E. face S 10, on S W. face and S 3 on NW. face. Also five notches on South and two notches on the East angles of the same for the corner to sections 2, 3, 10, and 11, from which
- A Laurel, 12 ins. diam., bears N.35*E., 55 lks.
Marked T 31 S R 5 W S 2 B T.
- A Fir, 22 ins. diam., bears S.35*E., 30 lks.
Marked T 31 S R 5 W S 11 B T.
- A Fir, 38 ins. diam., bears S.35*W., 13 lks.
Marked T 31 S R 5 W S 10 B T.
- A Dogwood, 7 ins. diam., bears N.15*W., 41 lks.
Marked T 31 S R 5 W S 3 B T.
- Land, mountainous
- Soil, rocky, third and fourth rate.
- Timber, Fir, Cedar, Laurel, Yew, and Maple.
- Thick undergrowth of Fir, Yew, Live Oak, and Hazel.
-
- Va. 19*E.
- East, on Random line between Secs. 2 & 11.
- 9.23 A Creek, 1 lks. wide, c N. steep ascent.
- 25.25 Top of high ridge, c NE. Descend.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 50.00 Steep descent.
- 70.50 Creek, 25 lks. wide, c N.
- 71.50 Saw Mill South 12 chs.