

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 5 W.

CHAINS

- 74.40 Wagon Road, c N.60*E.
- 74.80 Water flume for mill, c S.60*W.
- 79.35 Water flume for mill, c NW.
- 80.00 Canyon Creek, 30 lks. wide, c NW.
- 80.75 Intersect N. & S. line 35 lks. S. of corner to sections
1, 2, 11 & 12.
Thence, I run
S.89*45*W on true line between sections 2 & 11 with
same var.
- 40.37 Set Laurel post, 3 feet long, 3 ins. square, 18 ins. in
ground, marked 1/4 S on N. face for the 1/4 sec. cor.,
from which
A Laurel, 7 ins. diam., bears S.70*E., 8 lks.
Marked 1/4 S B T.
A Fir, 14 ins. diam., bears N.5*W., 24 lks. dis.
Marked 1/4 S B T.
- 80.75 The corner to sections 2, 3, 10 and 11.
Land, mountainous.
Soil, rocky, third rate.
Timber, dense growth of fir, Cedar, Yew, Laurel &
Maple.
Undergrowth, same kinds of wood.

Va. 19*E.

- North, on Random line between Sections 2 & 3.
- 6.45 A Creek, 1 lk. wide, c E.
- 12.50 Top of spur, c E. Descend.
- 20.00 A Creek, 2 lks. wide, c NE.
- 40.00 Set temp. 1/4 sec. cor.
- 71.50 Creek, 2 lks. wide, c NE.
- 81.40 Intersect North boundary of township 175 lks. West of
corner to sections 2, 3, 34 & 35, which is a stone,
18x12x6 ins. firmly set in ground, from which