

## County Surveyor's Record, Douglas County, Oregon.

Subdivisions of T. 31 S., R. 5 W.

CHAINS

From the cor. to secs. 4, 5, 32 and 33 on the S. bdy. of township, which is a post firmly set in ground,

4 ins. square, and marked

T 31 S R 5 W S 33 on NE. face.

T 32 S R 5 W S 4 on SE. face.

S 5 on the SW. face and S 32 on the NW. face, with 4 notches on the E. and 2 notches on the W. edges of same, from which

A fir, 8 ins. diam., bears S.53\*E., 6 lks. dist.

Marked T 32 S R 5 W S 4 B T.

A fir, 12 ins. diam., bears S.39\*W., 98 lks. dist.

Marked S 5 T 32 S R 5 W B T.

A fir, 9 ins. diam., bears N.30\*W., 13 lks. dist.

Marked T 31 S R 5 W S 32 B T.

Unable to find the witness tree for sec. 33

Thence I run

North, between secs. 32 and 33.

Va. 19\*E.

16.00 Begin descent.

Thence along SE. slope.

40.00 Set a basalt stone, 15x14x6 ins., 10 ins. in ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face, from which

A fir, 22 ins. diam., bears N.62\*E., 24 lks. dist.

Marked  $\frac{1}{4}$  S B T.

A fir, 5 ins. diam., bears S.75\*W., 18 lks. dist.

Marked  $\frac{1}{4}$  S B T.

48.90 A creek, 2 lks. wide, c NE. Ascend.

64.00 Top of ridge, c NE. Begin descent.

80.00 Set a stone, 14x12x6 ins., 10 ins. in ground, for the cor. to secs. 28, 29, 32 and 33, marked with one notch on the South and four on the East angles of the same, from which