

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 5 W.

CHAINS
40.40

Marked a fir tree, 4 ins. diam., with a blaze and $\frac{1}{4}$ S
on N. side for the $\frac{1}{4}$ sec. cor., from which

A fir, 5 ins. diam., bears N., 22 lks. dist.

Marked $\frac{1}{4}$ S B T.

A fir, 8 ins. diam., bears S.4*W., 18 lks. dist.

Marked $\frac{1}{4}$ S B T.

80.80

The cor. to secs. 8, 9, 16 and 17.

Lands, mountainous and broken.

Soil, rocky, third and fourth rates, covered with dense
forests of fir, cedar, and laurel timbers. Also
thick undergrowth of same kind of woods with maple,
hazel, dogwood and live-oak.

Va. 19*E.

North, on random line between secs. 8 and 9.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

48.00

A creek, 1 lk. wide, C S.10*W.

80.00

A point, 5.80 chains east of a point due South of the
established witness cor. to secs. 4 and 5, at which point,
I establish a witness cor. to secs. 8 and 9 by setting
a fir post, 4 ins. square, 20 ins. in ground, marked
T 31 S R 5 W on NE. face, S 9 on SE. face, S 8 on SW.
face and W.C. on NW. face, also five notches on the S.
and e notches on E. angles of same. Made stone mound,
3 ft. high, 4 ft. at base. Pits impracticable, unable to
reach Witness corner between secs. 3 and 4 to ascertain
the distance from this established witness corner.

I run S.4*09'E., on a true line between secs. 8 and 9,
with same var.

40.00

Set a stone, 15x10x6 ins., 10 ins. in ground, marked $\frac{1}{4}$
on W. face, for the $\frac{1}{4}$ sec. cor., from which

A fir, 6 ins. diam., bears N.52*E., 21 lks. dist.

Marked $\frac{1}{4}$ S B T.

A fir, 12 ins. diam., bears S.55*W., 24 lks. dist.