

County Surveyor's Record, Douglas County, Oregon

Subdivisions T. 31 S., R. 5 W.

CHAINS

A Fir, 24 ins. diam., bears S.6*W., 24 lks. dis.

Marked $\frac{1}{4}$ S B T.

A Fir, 24 ins. diam., bears N.5*W., 53 lks. dist.

Marked $\frac{1}{4}$ S B T.

80.72 The cor. to secs. 29, 30, 31 & 32.

Land, high mountainous.

Soil, third rate.

Timber, dense forest of Fir, Cedar, Pine and Laurel.

Undergrowth, same kind of wood with Maple, Hazel,

Dogwood and Arrow-wood.

Va. 19*45'E.

West, on Random line between secs. 30 & 31.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

84.53 Intersect W. bdy. of Township, 35 lks. North of cor.

to secs. 25, 30, 31 and 36, which is a post, 3 ins. square, firmly set in ground, marked

T 31 S R 5 W S 30 on NE. face, and S 31 on SE. face,

S 36 on SW. face, R 6 W S 25 on NW. face, also one

notch on S. and five notches on the N. angles of

the same, from which

A Fir, 20 ins. diam., bears N.38*W., 16 lks.

Marked T 31 S R 6 W S 25 B T.

A Yew, 14 ins. diam., bears N.31*E., 64 lks. dis.

Marked T 31 S R 5 W S 30 B T.

A Fir, 20 ins. diam., bears S.68*E., 95 lks. dis.

Marked T 31 S R 5 W S 31 B T.

A Fir, 36 ins. diam., bears S.33*W., 26 lks. dis.

Marked T 31 S R 6 W S 36 B T.

Thence, I run N.89*45'^E on true line between secs.

30 and 31 with same var.

Per research 6/1/75
D.C.S.O. X

44.53 Set a cedar post, 3 ins. square, 3 ft. long, 18 ins. in

ground for the $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on the N.

face, from which