

County Surveyor's Record, Douglas County, Oregon

7943

West Boundary of Township 31 S., Range 6 W., as surveyed
by Deputy Surveyor, George W. Hyde, under Contract No. 54,
dated February 19, 1855.

CHAINS		
	South, on the West Bdy. of sec. 6.	
5.00	Foot of Rocky Bluff.	+10
7.00	Top of Rocky Bluff.	+60
37.00	Top of Mt. ridge, S. of Cow Creek	+500
40.00	Set $\frac{1}{2}$ sec. post in dry rocky ravine, from which A Laurel, 6 ins. dia., bears N.57*E., 131 lks. dis A live Oak, 4 ins. dia., bears S.22*W., 52 lks. dis.	-100
61.00	Summit on line of E. slope of ridge	+380
70.00	Foot of dry ravine, course E.	-180
80.00	Set post cor. for secs. 1, 6, 7, and 12, from which A fir, 12 ins. dia., bears N.17*E., 118 lks. dis. A fir, 12 ins. dia., bears N.42*W., 82 lks. dis. A fir, 18 ins. dia., bears S.78*W., 109 lks. dis. (no other trees near)	+250
	Land, rough broken, mountainous, unfit for settlement. Timber, pine, fir, laurel, and some oak. Soil, 2nd rate, with some grass. Surface too much broken to be available.	
	Va. 17*45'E,	
	South, on the W. Bdy. of sec. 7.	
5.00	Top of ridge, course E. and W.	+120
34.50	Stream in canon, course W. Leave bald slope.	-400
40.00	Set $\frac{1}{4}$ sec. post, from which A Cedar, 20 ins. dia., bears S.48*W., 21 lks. dis. A Laurel, 10 ins. dia., bears N.78*E., 13 lks. dis.	+120
44.00	Summit on line of West slope.	+150
71.50	Branch, course West.	-480
77.40	A Fir 24 ins. dia.,	+250
80.00	Set post cors. to secs. 7, 12, 13 and 18, from which A Fir, 36 ins. dia., bears N.45*E., 16 lks. dis. A Fir, 36 ins. dia., bears S.22*E., 12 lks. dis.	+40