

7957

15

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 6 W.  
Same Deputy and Contract.

CHAINS

Beginning at the cor. to secs. 1, 2, 35 and 36, on the South Bdy. of Tp., which is a post, 3 ins. sq., set firmly in the ground and marked.

T 31 S R 7 W S 36 on NE.

T 32 S S 1 on SE.

S 2 on SW and,

S 35 on NW. faces, with 1 notch on E. and 5 notches on W. edges, from which

A Fir, 8 ins. dia., bears N.28°E., 6 lks. dis.

A Fir, 6 ins. dia., bears S.53°E., 50 lks. dis.

A Fir, 18 ins. dia., bears S.60°W., 47 lks. dis.

A Fir, 14 ins. dia., bears N.30°W., 59 lks. dis.

I run N. bet. secs. 35 and 36.

Va. 19°30'E.

Begin descent along W. slope of mountain.

40.00 Set a Chinkapin post, 3 ft long, 3 ins. sq., 15 ins. in the ground for  $\frac{1}{4}$  sec. cor. mkd.  $\frac{1}{4}$  S on W. face, from which

A Chinkapin, 8 ins. dia., bears S.40°E., 8 lks. dis.

A Laurel, 14 ins. dia., bears S.60°W., 20 lks. dis.

57.00 Spring, course West.

61.50 Spring, course SW.

63.00 Steep ascent.

80.00 Set Sugar Pine post, 4 ft. long, 4 ins. sq., 22 ins. in the ground for cor. to secs. 25, 26, 35 and 36 mkd.

T 31 S R 6 W S 25 on NE.

S 36 on SE.

S 35 on SW and,

S 26 on NW. faces with 1 notch on S. and E. edges, from which

A Fir, 18 ins. dia., bears N.36°E., 17 lks. dis.

mkd. T 31 S R 6 W S 25 B T.

A Fir, 24 ins. dia., bears S.55°E., 56 lks. dis.

mkd. T 31 S R 6 W S 36 B T.