

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 6 W.

CHAINS

A fir, 6 ins. diam., bears N.20*W., 35 lks. dist.
marked T 31 S R 6 W S 1 B T.

Thence I run

S.89*33'W., on true line, bet. secs. 1 and 12.

Va.18*30'E.

- 40.10 Set a fir post, 3 ft. long, 3 ins. sq., 20 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N face, from which
- A fir, 7 ins. diam., bears S.49*W., 47 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 22 ins. diam., bears N.20*E., 40 lks. dist., marked $\frac{1}{4}$ S B T.

- 80.20 The cor. to secs. 1, 2, 11 and 12.

Land, mountainous.

Soil, 3d rate.

Timber, fir, laurel and pine.

Thick undergrowth of fir, laurel, pine, hazel and balm.

Va.19*30'E.

North, on random line, bet. secs. 1 and 2.

Descend to

- 5.00 Dry ravine, course SW; ascend.
- 13.50 Top of spur, course W; descend.
- 19.00 Dry ravine, course W; moderate ascent.
- 38.00 Top of ridge, course NW.
- Descend along NE slope.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 81.50 Intersect Tp. line, 30 lks. W of cor. to secs. 1, 2, 35 and 36, which I re-established as per notes furnished, bearing trees all standing viz. Set a post, 4 ft. long, 4 ins. sq., 22 ins. in the ground for the cor. marked
- T 30 S R 6 W S 36 on NE
- T 31 S S 1 on SE.
- S 2 on SW and
- S 35 on NW face, with 1 notch on E and 5 notches on W edges, from which