

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 6 W.

CHAINS

S 33 on NW. faces, with 3 notches on E. and W. edges.

Bearing trees all standing, viz.

A B. Oak, 21 ins. dia., bears N.30*E., 125 lks. dis.
mkd. T 30 S R 6 W S 34 B T.

A B. Oak, 20 ins. dia., bears S.85*E., 104 lks. dis.
mkd. T 31 S R 6 W S 3 B T.

A B. Oak, 20 ins. dia., bears S.26*W., 62 lks. dis.
mkd. T 31 S R 6 W S 4 B T.

A B. Oak, 20 ins. dia., bears N.18*W., 109 lks. dis.
mkd. T 30 S R 6 W S 33 B T.

Thence I run S. ^{33'}33*W., on true line bet. secs. 3 and 4.

Va. 17*30'E.

41.40 Set Fir post 3 ft. long, 3 ins. sq., 18 ins. in the ground for 1/4 sec. cor. mkd. 1/4 S on W. Face, from which

A Fir, 10 ins. dia., bears S.40*E., 49 lks. dis.
mkd. 1/4 S B T.

A Fir, 16 ins. dia., bears N.68*W., 20 lks. dis.
mkd. 1/4 S B T.

81.40 The cor. to secs. 3, 4, 9 and 10.

Land, broken, mostly sloping W.

Soil; 3rd rate.

Timber, Fir, Laurel, Pine and Oak.

Thick undergrowth of Fir, Laurel, Pine and Oak.

July 11, 1882

From the cor. to secs. 4, 5, 32 and 33, on S. Bdy. of the Tp. which is a post 4 ins. sq., set firmly in the ground and mkd.

T 31 S R 6 W S 33 on NE.

T 32 S S 4 on SE.

S 5 on SW., and

S 32 on NW. faces, with 4 notches on E. edges, and 2 notches on W. edges, from which