

## County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 31, S. R. 7 W.,

CHAINS

East on Random line, bet. secs. 13 and 24.

Va. 19\*E.

Descend.

5.50 Along sidehill, facing N.

40.00 Set temp.  $\frac{1}{4}$  Sec. cor.

60.00 Trail on top of ridge, C. SW.

80.40 Intersect Tp. line 70 lks. S. of cor. to secs. 13, 18, 19 and 24, which is a post, 4 ins. sq., set firmly in the ground and marked T 31 S R 6 W S 18 on NE., S 19 on SE; R 7 W S 24 on SW and S 13 on NW faces, with 3 notches on N. and S. edges, from which

A Cedar, 16 ins. diam., bears N.22\*E., 62 lks. dist.

Marked T 31 S R 6 W S 18 B T.

A Fir, 8 ins. diam., bears S.62\*E., 30 lks. dist.

Marked T 31 S R 6 W S 19 B T.

A Fir, 48 ins. diam., bears S.72\*W., 50 lks. dist.

Marked T 31 S R 7 W S 24 B T

A Fir, 10 ins. diam., bears N.20\*W., 20 lks. dist.

Marked T 31 S R 7 W S 13 B T.

Thence I run S.89\*30\*W., on true line bet. secs. 13 and 24.

40.20 Set fir post, 3 ft. long, 3 ins. sq., 18 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on N. face from which

A Cedar, 30 ins. diam., bears N.10\*W., 36 lks., dist.

Marked  $\frac{1}{4}$  S B T.

A Fir, 12 ins. diam., bears S.26\*E., 28 lks. dist.

Marked  $\frac{1}{4}$  S B T.

80.40 The cor. to secs. 13, 14, 23 and 24.

Land, mountainous,. Soil, 3rd rate.

Timber, mostly Fir, with some pine, laurel and cedar.

Thick undergrowth of fir, laurel, pine and cedar.

July 23rd, 1882.