

## County Surveyor's Record, Douglas County, Oregon

Retracement Portion West Bdy., T. 31 S., R. 7 W.,  
 Executed by Gerald A. Sorrels, in the capacity  
 Of U.S. Surveyor, under Special Instructions,  
 Dated March 1st, 1917.

CHAINS

I commence at the cor. of secs. 1, 6, 7 and 12, on the W.  
 bdy. of the Tp., the point for which is located by  
 reference to the bearing trees, the NE. tree having  
 fallen. At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
 the ground, for cor. of secs. 1, 6, 7 and 12, with  
 brass cap marked

T31S
R8W R7W
S1 S6
S12 S7
1918

from which

A Fir, 8 ins. diam., bears N.85°E., 43 lks. dist.,  
 marked T 31 S R 7 W S 6 B T (New B.T.)

A Fir, 10 ins. diam., bears S.20°E., 50 lks. dist.  
 marked T 31 S R 7 W S 7 B T (Old B.T.)

A Fir, 14 ins. diam., bears S.46°W., 21 lks. dist.,  
 marked T 31 S R 8 W S 12 B T (Old B.T.)

A Fir, 16 ins. diam., bears N.19°W., 26 lks. dist.,  
 marked T 31 S R 8 W S 1 B T (Old B.T.)

Thence

North, retracing the line bet. secs. 1 and 6.

Ascend SW. slope, through heavy timber and dense under-  
 growth.

9.80 Top of spur, slopes SW.; descend.  
 15.30 Ravine, course SW.; ascend.  
 21.60 Top of spur, slopes SW.; descend.  
 32.50 Rocky point, slopes W.  
 40.84 Fall, 5 lks. E. of the point for old  $\frac{1}{2}$  sec. cor., located  
 by reference to the bearing trees. The NW. tree fallen.  
 At the exact cor. point,  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins.  
 in the ground, for  $\frac{1}{2}$  sec. cor., with brass cap marked

S1	↑	S6
1918		