

Retracement Portion Subdivisions, T.31 S., R.7 W.,

CHAINS

I commence at the cor. of secs. 3, 4, 9 and 10, the point for which is located by reference to the bearing trees.

At the exact cor. point,

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap marked

| | |
|------|-----|
| T31S | R7W |
| S4 | S3 |
| S9 | S10 |
| 1918 | |

from which

A Fir, 24 ins. diam., bears N.77*E., 40 lks. dist.,

Marked T 31 S R 7 W S 3 B T (Old B.T.)

A White Oak, 8 ins. diam., bears S.57*E., 27 lks.

dist., marked T 31 S R 7 W S 10 B T (Old B.T.)

A Black Oak, 12 ins. diam., bears S.33*W., 23 lks.

dist., marked T 31 S R 7 W S 9 B T (Old B.T.)

A Fir, 20 ins. diam., bears N.8*W., 29 lks. dist.,

Marked T 31 S R 7 W S 4 B T (Old B.T.)

Thence

North, retracing the line bet. secs. 3 and 4.

Along gentle W. slope, through heavy timber and dense undergrowth.

- 1.70 Top of spur, slopes W.; descend.
 - 6.95 Creek, 2 lks. wide, course W.; ascend.
 - 13.80 Top of rocky spur, slopes W.; descend. Steep N. slope.
 - 19.90 Ravine, course W.; ascend over conglomerate bedrock.
 - 25.20 Top of rocky spur, slopes S.70*W.; descend over bluff.
 - 27.50 Rift in rocks, course W.; ascend.
 - 33.00 Top of spur, slopes W.; descend.
 - 35.50 Foot of bluffs, 250 Ft. high.
 - 38.70 Fall 203 lks. W. of the old $\frac{1}{4}$ sec. cor., located by reference to the bearing trees. At the exact cor. point
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked