

Retracement Portion Subdivisions, T.31 S., R.7 W.,

CHAINS

ground, for cor. of secs. 4, 5, 8 and 9, with brass cap marked

T31S	R7W
S5	S4
S8	S9
1918	

from which

A yellow pine, 50 ins. diam., bears N.59°E., 76 lks. dist., marked T 31 S R 7 W S 4 B T (Old B.T.)

A yellow pine, 20 ins. diam., bears S.79°E., 103 lks. dist. marked T 31 S R 7 W S 9 B T (New B.T.)

A yellow pine, 20 ins. diam., bears S.15°W., 55 lks. dist., marked T 31 S R 7 W S 8 B T (New B.T.)

A white oak, 10 ins. diam., bears N.47°W., 65 lks. dist. marked T 31 S R 7 W S 5 B T (New B.T.)

The true course and length of this line from the 1/4 sec. cor. is S.89°15'W., 41.02 chs.

Land, mountainous.

Soil, sandy clay loam on slopes; gravel and sand in creek bottom; 2nd and 3rd rate.

Timber, fir, yellow pine, white oak and black oak.

Undergrowth, fir, willow and chaparral.

S.89°51'W., retracing the line bet. secs. 5 and 8.

Ascend E. slope. through heavy timber and dense undergrowth.

3.85 Top of spur, slopes SE.; ascend along S. slope.

17.35 Top of rock point, slopes S.; descend.

20.25 Ravine, course S.; ascend.

28.60 Top of spur, slopes SE.; descend.

31.85 Ravine, course S.

36.00 Top of spur, slopes S.; descend W. slope.

39.89 Fall 9 lks. N. of the point for old 1/4 sec.cor., located by reference to the bearing trees. At the exact cor. point,

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the