

Retracement Portion Subdivisions, T.31 S., R.7 W.,

CHAINS

ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$  S5  
      
 S8  
 1918

from which

A black oak, 18 ins. diam., bears N.22\*E., 51 lks. dist., marked  $\frac{1}{4}$  S 5 B T (Old B.T.)

A black oak, 15 ins. diam., bears S.31\*E., 45 lks. dist., marked  $\frac{1}{4}$  S 8 B T (Old B.T.)

The true course and length of this line is S.89\*43'W., 39.89 chs.

I continue my retracement S.89\*51'W., from the  $\frac{1}{4}$  sec.cor., counting distance from the sec. cor.

- 55.10 Creek, 2 lks. wide, course S.15\*W.; ascend.
- 57.35 Top of spur, slopes S.; descend.
- 57.95 Wire fence, bears NW. and SE.
- 58.70 Ravine, course SE.; ascend.
- 61.45 Top of spur, slopes S.; trail along top; descend.
- 68.40 Enter clearing, bears N. and S.
- 69.15 Table Creek, 15 lks. wide, course S.; road along creek.
- 73.40 Wire fence, bears N. and S.; enter timber and undergrowth. Ascend steep E. slope.
- 77.82 Fall 132 lks. N. of the point for cor. of secs. 5, 6, 7 and 8, located by reference to the bearing trees. At the exact cor. point  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, with brass cap marked

T31S | R7W  
  S6 | S5    
  S7 | S8    
 1918

from which

A fir, 30 ins. diam., bears N.31\*E., 51 lks. dist., marked T 31 S R 7 W S 5 B T (New B.T.)

A fir, 36 ins. diam., bears S.72\*E., 56 lks. dist.,