

County Surveyor's Record, Douglas County, Oregon

8093
15

Retracement Portion Subdivisions, T.31S., R.7 W.,

CHAINS	<p>dist., marked W C T 31 S R 7 W S 4 B T.</p> <p>Ascend over bluffs.</p> <p>78.08 Intersect the N. bdy. of the Tp., 3.88 chs. S.88°18'W., of the cor. of secs. 32 and 33, point for cor. of secs. 4 and 5, impracticable to establish cor.</p> <p>Land, mountainous.</p> <p>Soil, to 68.00 chs. gravelly black loam, 2nd rate: remainder, solid rock, 4th rate.</p> <p>Timber, fir, white oak, black oak, yellow pine and live oak.</p> <p>Undergrowth, live oak, poison oak, chaparral and fir.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>North, retracing the line bet. secs. 5 and 6.</p> <p>Ascend S. slope, through heavy timber and dense undergrowth.</p> <p>1.35 Low spur, slopes SE.; descend NE. slope.</p> <p>7.10 Wire fence, bears NW. and SE.; enter clearing.</p> <p>15.15 Wire fence, bears NW and SE.</p> <p>16.25 Table Creek, 15 lks. wide, course SE.</p> <p>18.40 Logsdon's house bears N.38°W.; 5.00 chs. dist. Barn bears S.60°W., 1.30 chs. dist.</p> <p>18.60 Picket fence, bears E. and W.</p> <p>23.50 Rail fence, bears N.70°W. and S.70°E.</p> <p>Leave clearing; ascend SW. slope, through heavy timber and dense undergrowth.</p> <p>30.70 Top of spur, slopes SW.; descend NW. slope.</p> <p>40.05 Fall 42 lks. W. of the point for old $\frac{1}{4}$ sec. cor., located by reference to the bearing trees. At the exact cor. point</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$ S6 S5 1918</p> <p>from which</p>