

South Boundary of T. 31 S., R. 8 W.,  
 as surveyed by Wm H. Byars, Deputy Surveyor,  
 under Contract No. 456, dated July 28th, 1882.

CHAINS

I begin at the corner to Tps. 31 & 32 S., Rs 7 & 8 W.,  
 which is a post 4 in. sq. firmly set in the ground  
 and marked, T. 31 S & S 31 on NE; R. 7 W S 6 on SE.,  
 T 32 S S 1 on SW., & R 8 W S 36 on NW. faces, with  
 6 notches on each angle of same, from which

A Fir, 24 in. in diam., bears N.42\*E., 40 lks. dist.

Marked T 31 S R 7 W S 31 B T

A Live Oak, 8 in. in diam., bears S.78\*E., 61 lks.

Marked T 32 S R 7 W S 6 B T

A Live Oak, 8 in. in diam., bears S.45\*W., 40 lks.

Marked T 32 S R 8 W S 1 B T

A Fir, 12 in. in diam., bears N.38\*W., 97 lks.

Marked T 31 S R 8 W S 36 B T

Thence I run

West bet. Secs. 1 & 36.

Va. 19\*East.

Steep Descent.

- 4.10 A Creek, 3 lks. wide, course S. Ascend.
- 10.50 Top of Spur, course S. Descend.
- 19.00 A Creek, 3 lks. wide, course SE. Ascend.
- 30.50 Top of Spur, course SE.
- 40.00 Set a Fir post 3 ft. long, 3 ins. sq., 18 ins. in the  
 ground marked  $\frac{1}{4}$  S on the N. side for the  $\frac{1}{4}$  Sec. Cor.,  
 from which Marked  $\frac{1}{4}$  S B T  
 A Laurel, 6 in. in diam., bears S.62\*E., 33 lks.  
 A Laurel, 6 in. in diam., bears N.30\*W., 38 lks.  
 Marked  $\frac{1}{4}$  S B T
- 46.80 A Creek, 1 lk. wide, course SE. Steep Ascent.
- 63.00 Top of Spur, course S.
- 76.50 Top of Ridge and old trail, course SW. Steep Descent.
- 80.00 Set a pine post 4 ins. sq. 4 ft. long, 24 ins. in the  
 ground, marked T 31 S R 8 W S 36 on NE., T 32 SS 1  
 on the SE., S 2 on SW., and S 35 on the NW. faces.  
 Also 1 notch on the E. and 5 notches on the W. angles  
 of same, for the cor. to Secs. 1, 2, 35 & 36, and