

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 31 S., R. 8 W.

CHAINS	Mountain balm.	Nov. 19th, 1882.
	West bet. Secs. 6 & 31.	Var. 19* East.
	Steep Ascent.	
6.50	Top of Spur, course S. Descend.	
40.00	Set a stone 16x14x10 ins., 8 ins. in the ground, marked $\frac{1}{4}$ on N. side for the $\frac{1}{4}$ sec. cor., from which A Fir, 30 ins. diam., bears S.10*W., 12 lks. dist. Marked $\frac{1}{4}$ S B T A Fir, 32 ins. diam., bears N.30*W., 35 lks. dist. Marked $\frac{1}{4}$ S B T	
42.80	A Creek, 5 lks. wide, course S.	
80.00	Set temp. corner.	Nov. 20th, 1882.
92.60	The point of intersection and established corner as described below. (West Bdy. of T. 31 S., R. 8 W.) Land, mountainous. Soil, 3d rate. Timber: Dense forest of fir, pine, laurel, cedar and Chincapin. Undergrowth: Chiefly fir, pine, laurel, cedar and Chincapin.	November 23d, 1882.
	West Boundary of T. 31 S., R. 8 W., same Deputy and Contract.	
	To establish the Corner for Tps. 31 & 32 S. Rs. 8 & 9 W., I begin at the established corner for Tps. 30 & 31, S. Rs. 8 & 9 W., which is a post 4 in. sq., firmly set in the ground, and marked T 30 S S 31 on NE. face, R 8 W S 6 on SE. face T 31 S S 1 on SW face and R. 9 W S 36 on NW. face, from which A Fir, 12 ins. diam., bears N.2*E., 43 lks. dist. Marked T 30 S R 8 W S 31 B T	