

## Subdivisions of T. 31 S., R. 8 W.

CHAINS

From the Cor. to Secs. 2, 3, 34 & 35 on the South  
Boundary of the Township, which is a Stone 18x14x10 ins.  
firmly set in the ground and marked, 2 notches on E.  
and 4 notches on W. edges, from which

A Fir, 14 ins. diam., bears N.82\*E., 57 lks. dist.

Marked T 31 S R 8 W S 35 B T

A Fir, 14 ins. diam., bears S.65\*E., 41 lks. dist.

Marked T 32 S R 8 W S 2 B T

A Fir, 16 ins. diam., bears S.28\*W., 30 lks. dist.

Marked T 32 S R 8 W S 3 B T

A Fir, 13 ins. diam., bears N.35\*W., 42 lks. dist.

Marked T 31 S R 8 W S 34 B T

North bet. Secs. 34 & 35.

Va. 19\*East.

- 4.20 A Creek, 3 lks. wide, course E. Steep Ascent.
- 9.00 Top of Spur, course E. along steep E. slope.
- 40.00 Set Maple post 3 ft. long, 3 in. sq., 18 ins. in the  
ground, marked  $\frac{1}{4}$  S on W. side, from which
- A Fir, 30 ins. diam., bears S.68\*E., 50 lks. dist
- Marked  $\frac{1}{4}$  S B T
- A Fir, 20 ins. diam., bears N.24\*W., 41 lks. dist.
- Marked  $\frac{1}{4}$  S B T
- 42.00 Steep Descent.
- 56.00 A Creek, 2 lks. wide, course E. Trail course SE.
- 65.25 R. Road 10 lks. E. of line.
- 66.60 A Creek, 2 lks. wide, course E.
- 75.75 A Creek, 6 lks. wide, course SE.
- 80.00 Set a Laurel post 4 ft. long, 4 ins. sq., 20 ins. in the  
ground, marked T 31 S R 8 W S 26 on NE., S 35 on SE.,  
S 34 on SW., and S 27 on NW. Also 1 notch on S. and  
2 on the E. angles of same, for the cor. to Secs. 26,  
27, 34 & 35, from which
- A Laurel, 10 ins. diam., bears N.14\*E., 30 lks. dist
- Marked T 31 S R 8 W S 26 B T