

County Surveyor's Record, Douglas County, Oregon

SOUTH BOUNDARY OF T. 31 S., R. 9 W.

CHAINS

West, on South boundary of Sec. 32.

Ascend E. slope of mountain.

14.00 Old $\frac{1}{4}$ Sec. cor.

Corner and witness trees standing.

40.00 Set a Basalt stone 20x14x4 ins. 15 ins. in the ground,
marked $\frac{1}{4}$ on N. face for the $\frac{1}{4}$ sec. cor. of Sec. 32,
from whichA Fir, 14 ins. diam., bears N.30*E., 167 lks.
dist., marked S 32 $\frac{1}{4}$ S B T.A Fir, 48 ins. diam., bears S.70*E., 74 lks.
dist., marked S 32 $\frac{1}{4}$ S B T.

Top of ridge, course N and S. Steep descent.

+600

54.00 Cor. of Secs. 5 and 6. Corner and witness trees
standing.

69.40 A creek 20 lks. wide, course N.20*E.

-600

70.00 Steep ascent.

80.00 Set a stone 16x10x5 ins. 12 ins. in the ground, for
cor. to Secs. 31 and 32, marked with 5 notches on
the E. and 1 notch on the W. angle, from which

+300

A Yew, 6 ins. diam., bears N.15*E., 42 lks. dist.
marked T 31 S R 9 W S 32 B T.A Yew, 6 ins. diam., bears N.32*W., 49 lks. dist.,
marked T 31 S R 9 W S 31 B T.

Land, mountainous.

Soil, rocky, 3rd and 4th rate.

Timber, Fir, Cedar, Hemlock, Chinquapin and Yew.

Undergrowth, heavily timbered or covered with dense
undergrowth. 80.00 chains.

West, on South boundary of Sec. 31.

13.00 Old $\frac{1}{4}$ Sec. corner and witness trees standing.40.00 Set a stone, 18x12x6 ins. 12 ins. in the ground, marked
 $\frac{1}{4}$ on N. face for the $\frac{1}{4}$ Sec. cor. for Sec. 31,
from which