

SUBDIVISIONS OF T. 31 S., R. 9 W.

| CHAINS |   |      |
|--------|---|------|
|        | N.0*02'W bet. Secs. 15 and 16.<br>Along E. slope of mountain. Ascend.   |      |
| 15.00  | Summit of Panther Ridge, course N.10*E and S.10*W.  | + 50 |
|        | Descend along W. slope of mountain.   |      |
| 40.00  | Set a Fir post, 4 ft. long, 4 ins. sq. 24 ins. in the ground, marked S 15 on E and S 16 1/4 S on W for 1/4 Sec. cor. from which<br>A Fir, 16 ins. diam., bears N.70*E., 14 lks. dist., marked S 15 1/4 S B T.<br>A Fir, 12 ins. diam., bears S.62*W., 22 lks. dist., marked S 16 1/4 S B T.   |      |
| 50.00  | Head of draw, course W.   | - 50 |
| 51.75  | A spur, course W.   | + 25 |
| 53.50  | Draw, course W.   | - 25 |
| 55.00  | Spur, course W.   | + 25 |
| 57.00  | Draw, course W.   | - 25 |
| 63.00  | Spur, course W.   | + 50 |
| 80.00  | Set a stone, 16x8x6 ins. 12 ins. in the ground, for cor, to Secs. 9, 10, 15 and 16, marked with 4 notches on S and 3 notches on E edges, from which<br>A Fir, 12 ins. diam., bears N.50*E., 109 lks. dist., marked T 31 S R 9 W S 10 B T.<br>A Fir, 30 ins. diam., bears S.42*E., 80 lks. dist., marked T 31 S R 9 W S 15 B T.<br>A Fir, 30 ins. diam., bears S.35*W., 46 lks. dist., marked T 31 S R 9 W S 16 B T.<br>A Fir, 20 ins. diam., bears N.40*W., 77 lks. dist., marked T 31 S R 9 W S 9 B T. | -200 |
|        | Land, mountainous.<br>Soil, rocky and clay, 3rd rate.<br>Heavily timbered Fir, Cedar, Pine, Hemlock, Chinquapin and Laurel.<br>Undergrowth, Fir, Cedar, Pine, Hemlock, Chinquapin, Balm and Vinemaple.  |      |