

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 32 S., R. 1 W., W. M.

CHAINS

A Fir, 40 ins. diam., bears S.30\*E., 14 lks. dist.  
mkd.  $\frac{1}{4}$  S B T, and

Set a basalt stone 15x12x12 ins. 10 ins. in the ground  
for closing cor. to secs. 1 and 6. T 32 S R 1 W,  
mkd. C C on S with 6 notches on S, E, and W, edges,  
from which

A Fir, 15 ins. diam., bears N.70\*E., 11 lks. dist.  
mkd. C C T 31 S R 1 W S 31 B T.

A Fir, 55 ins. diam., bears S.55\*E., 5 lks. dist.  
mkd. C C T 32 S R 1 W S 6 B T.

A Fir, 35 ins. diam., bears S.37\*W., 15 lks. dist.  
mkd. C C T 32 S R 2 W S 1 B T.

Land, high and mountainous; Soil, 2nd and 3rd rate.  
Densely covered with forests of fir, sugar pine and cedar.

98.05 chs.

Thick undergrowth of fir, vine maple, yew and arrowwood,  
and some live oak. Nov. 30, 1883.

Subdivisions of T. 32 S., R. 1 W., W. M.  
Same deputy and Contract.

Va.20\*15'E.

North, bet. secs. 23 and 24.

\* \* \* \* \*

80.00 Set a basalt stone, 14x9x8, ins., 10 ins. in the ground  
for cor. to secs. 13, 14, 23 and 24, 200 ft. above  
spring branch, mkd. with 3 notches on S. and 1 notch  
on E. edge, from which

A Fir, 25 ins. diam., bears N.38\*E., 26 lks. dist.  
mkd. T 32 S R 1 W S 13 B T.

A Fir, 22 ins. diam., bears S.66\*E., 19 lks. dist.  
mkd. T 32 S R 1 W S 24 B T.

A Fir, 20 ins. diam., bears S.10\*W., 23 lks. dist.  
mkd. T 32 S R 1 W S 23 B T.

A Fir, 24 ins. diam., bears N.56\*W., 24 lks. dist.  
mkd. T 32 S R 1 W S 14 B T.