

12  
County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 1 W., W. M.

## CHAINS

- 43.50 Top of Umpqua divide and ridge bears N.20\*W., and S.20\*E about 100 ft. above  $\frac{1}{4}$  sec. cor. and descend.
- 80.10 Intersect N. and S. line, 7 lks. S. of the cor. to secs. 11, 12, 13 and 14, about 400 ft. below top of Umpqua divide.
- Thence I run  
S.89\*57\*W., on a true line bet. secs. 11 and 14.  
Va.19\*E.
- 40.05 Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. mkd.  $\frac{1}{4}$  S on N. face, from which  
A Fir, 20 ins. diam., bears N.45\*W., 7 lks. dist.  
mkd.  $\frac{1}{4}$  S B T.  
A Fir, 14 ins. diam., bears S.5\*W., 20 lks. dist.  
mkd.  $\frac{1}{4}$  S B T.
- 80.10 The cor. to secs. 10, 11, 14 and 15.  
Land, high and mountainous; Soil, 3rd rate.  
Densely covered with forests of fir and sugar pine.  
80.10 chs.  
Thick undergrowth of fir, chinquapin, arrowwood, and Hazel and vine maple.
- 
- Va.19\*30'E.
- North, bet. secs. 10 and 11.  
Through timber.
- 18.00 Spring branch, 5 lks. wide, runs NW. about 300 ft. below sec. cor.
- 40.00 Set a maple post, 3 ft. long, 3 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. about 200 ft. below spring branch, mkd.  $\frac{1}{4}$  S on W. face, from which  
A fir, 6 ins. diam., bears East 13 lks. dist.  
mkd.  $\frac{1}{4}$  S B T.  
A fir, 6 ins. diam., bears N.62\*W., 23 lks. dist.  
mkd.  $\frac{1}{4}$  S B T.
- 48.90 Ravine, course W. and ascend.
- 66.00 Top of ridge, bears NE and SW., about 300 ft. above last ravine. and descend