

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 32 S., R. 1 W., W. M.

CHAINS	
	N. and S. and descend.
40.00	A point about 200 ft. below top of ridge and set temp. $\frac{1}{2}$ sec. cor.
78.50	Spring branch, 2 lks. wide, runs NE.
80.12	Intersect N. and S. line 42 lks. S. of the cor. to secs. 22, 23, 26 and 27 at a point about 300 ft. below $\frac{1}{4}$ sec. cor.
	Thence I run S.89°42'W., on a true line bet. secs. 22 and 27. Va.20°E.
40.06	Set a basalt stone 12x12x6 ins., 8 ins. in the ground for $\frac{1}{2}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, from which A fir, 28 ins. diam., bears N.28°E., 14 lks. dist. mkd. $\frac{1}{4}$ S B T. A fir, 40 ins. diam., bears S.60°W., 8 lks. dist. mkd. $\frac{1}{4}$ S B T.
80.12	The cor. to secs. 21, 22, 27 and 28. Land, high and mountainous; Soil, 3rd rate. Densely covered with forests of fir. 80.12 chs. Thick undergrowth of fir, chinquapin and vine maple.
	Va.20°E. North, bet. secs. 21 and 22.
40.00	Set a basalt stone 18x8x4 ins., 12 ins. in the ground for $\frac{1}{2}$ sec. cor. mkd. $\frac{1}{4}$ on W. face, from which A fir, 6 ins. diam., bears N.23°W., 15 lks. dist. mkd. $\frac{1}{4}$ S B T. A fir, 14 ins. diam., bears S.80°E., 21 lks. dist. mkd. $\frac{1}{4}$ S B T.
43.30	Spring on line runs W.
55.00	A point about 400 ft. above $\frac{1}{4}$ sec. cor. and Umpqua divide and top of ridge, bears NW and SE., and descend.
66.60	Spring branch, 3 lks. wide, runs NE. about 250 ft. below top of divide.